

AFRC Combat Camera Senior Leader Kit

Minimum Salient Characteristics

***NOTE: EACH KIT IS COMPRISED OF THE ITEMS BELOW AND MUST BE DELIVERED AS A COMPLETE KIT (ALL ITEMS AT ONCE), GRAY MARKET ITEMS ARE NOT ACCEPATBLE, USA MANUFACTUERS WARRANTY ONLY.**

AFRC Combat Camera Senior Leader Kit Includes:

Nikon 1 V3, 27695, 18.4MP Mirrorless Camera (OR EQUAL):

CX-Format CMOS Sensor, EXPEED 4A Image Processor, Includes NIKKOR VR 10-30mm f/3.5-5.6 PD-ZOOM Lens, 3.0" 1,037k-Dot Tilting Touchscreen LCD, Full HD 1080p Video Recording at 60 fps, Built-In Wi-Fi Connectivity, Hybrid AF System, ISO 12800 and Movie e-VR Stabilization, 20 fps Shooting with Full-Time AF, Electronic Viewfinder and Grip, Requires microSD/microSDHC/microSDXC Memory Card, Built-in Mic, Optional External Mic, Hot Shoe Mount, Includes 1x EN-EL20a Rechargeable 7.2 VDC/1110 mAh Lithium-ion Battery Pack, Nikon MH-29 Battery Charger, DF-N1000 Electronic Viewfinder, GR-N1010 Grip, UC-E20 Micro USB Cable, Approximate Dimensions 1/2" x 2 1/2" x 1 1/4", Approximate Weight 11 1/2 oz., Black. USA PART NUMBER ELIGIBLE FOR USA MANUFACTURER WARRANTY, NO GRAY MARKET ITEMS, AUTHORIZED DISTRIBUTOR ONLY.

Nikon 94049, CB-N4010SA Body Case Set for 1 V3 Camera, Black (OR EQUAL):

Nikon 94049, CB-N4010SA Body Case Set for 1 V3 Camera, Black (OR EQUAL): Soft case designed to accommodate the Nikon 1 V3 mirrorless digital camera with attached 1 NIKKOR VR 10-30mm f/3.5-5.6 PD-ZOOM or 1 NIKKOR 11-27.5mm f/3.5-5.6 lens. A two-part design permits use of the camera when the lens jacket is removed and an integrated 1/4"-20 mount permits attachment to a tripod. Approximate Weight 2 1/2 oz., Approximate Dimensions (LxWxH) 5 x 5 x 3 1/2". USA PART NUMBER ELIGIBLE FOR USA MANUFACTURER WARRANTY, NO GRAY MARKET ITEMS, AUTHORIZED DISTRIBUTOR ONLY.

Nikon EN-EL20a Battery, 3767, Lithium-Ion, 7.2V, 1100mAh (OR Equal):

F/u/w Nikon 1 V3 Mirrorless Digital Camera, Approximate Dimensions 2 3/4 x 2 1/4 x 1 1/4". Can be charged or discharged continuously without developing memory effect, can be charged with the MH-29 battery charger. USA PART NUMBER ELIGIBLE FOR USA MANUFACTURER WARRANTY, NO GRAY MARKET ITEMS, AUTHORIZED DISTRIBUTOR ONLY.

Nikon 1 SB-N7, Speedlight, 3710, i-TTL Shoe Mount, For Nikon 1 Series Cameras (OR EQUAL):

Compatible with Nikon i-TTL, 59' at ISO 100 Guide Number, 10mm (CX Format) Coverage, 1/1650 sec Flash Duration, Wide-Flash Adapter for 6.7mm Coverage, SW-N7 Wide Panel For SB-N7 Speedlight, BS-N2000 Mounting Foot Cover, SS-DC1 Polyester Soft Case, Tilts Upward 120°, 3.5-30 Seconds Recycle Time, Slow/1st & 2nd Curtain Sync, Runs on 2 AAA Batteries, Approximate Dimensions 2 1/4" x 2 1/2" x 2 1/2", Approximate Weight 4 1/4 oz., Black. USA PART NUMBER ELIGIBLE FOR USA MANUFACTURER WARRANTY, NO GRAY MARKET ITEMS, AUTHORIZED DISTRIBUTOR ONLY.

Nikon 3312, Lens, 30-110mm, F/u/w Nikon 1 Mount Lens (OR EQUAL):

Focal Length 30-110mm, Comparable 35mm Equivalent on CX Format Focal Length: 81-297 mm, Aperture Maximum f/3.8-5.6, Minimum f/16, Nikon 1 Type Mount, Nikon CX Format, Angle of View 29° 40'-8° 20', Minimum Focus Distance 3.28', Elements/Groups 18/12, Diaphragm Blades 7, Rounded, Image Stabilization, Autofocus, Filter Thread Front 40.5 mm, Approximate Dimensions (DxL) 2 1/2 x 2 1/2", Approximate Weight 6 1/4 oz., Black. USA PART NUMBER ELIGIBLE FOR USA MANUFACTURER WARRANTY, NO GRAY MARKET ITEMS, AUTHORIZED DISTRIBUTOR ONLY.

Nikon 3613, FT1 Mount Adapter, Nikon 1 to Nikkor F-mount Lenses (OR EQUAL):

AF/AE supported with AF-S lenses only, Vibration reduction (VR) functions when VR lenses are used, Black, Approximate Weight 1/2 lb., Approximate Dimensions (LxWxH) 4 1/2 x 4 x 3 3/4". USA PART NUMBER ELIGIBLE FOR USA MANUFACTURER WARRANTY, NO GRAY MARKET ITEMS, AUTHORIZED DISTRIBUTOR ONLY.

AFRC Combat Camera Senior Leader Kit

Minimum Salient Characteristics

SanDisk SDSQXWG-032G-ANCMA, Memory Card: microSDHC, 32GB (OR EQUAL):

Card Type microSDHC, Storage Capacity 32 GB, Speed Class 10, UHS Speed Class U3, Bus Interface Speed UHS Class I, Data Transfer Read Speed 95 MB/s Maximum, Write Speed 90 MB/s Maximum, Write Speed 30 MB/s Minimum, Durability; Shockproof, Temperature Extremes, Waterproof, X-Ray Proof, and Built-in Write-Protection Switch. Includes Rescue-PRO Deluxe data recovery software downloadable offer, for bringing accidentally deleted images back to file. USA PART NUMBER ELIGIBLE FOR USA MANUFACTURER WARRANTY, NO GRAY MARKET ITEMS, AUTHORIZED DISTRIBUTOR ONLY.

Lexar LRW025URBNA, Memory Card Reader, Multi-Card: 25-in-1, USB 3 (OR EQUAL):

500MB/s Transfer Speed, For CompactFlash Type I and Type II, SD / SDHC / SDXC, miniSD / miniSDHC, MMC, MMCplus, RS-MMC, microSD/microSDHC, Memory Stick, Memory Stick with MagicGate, Memory Stick PRO, Memory Stick PRO Duo, Memory Stick Duo with MagicGate, Memory Stick PRO Duo Mark 2, Memory Stick PRO-HG Duo, Memory Stick PRO-HG Duo HX, Memory Stick Micro (M2), xD-Picture Card, xD-Picture Card Type-M, xD-Picture Card Type-M+, and xD-Picture Card Type-H Concurrent Downloads, Card-to-Card File Transfer. USA PART NUMBER ELIGIBLE FOR USA MANUFACTURER WARRANTY, NO GRAY MARKET ITEMS, AUTHORIZED DISTRIBUTOR ONLY.

Rode STEREO VIDEOMIC PRO, Microphone, Compact, Shotgun (OR EQUAL):

Stereo, Integrated Shoemount/Shockmount, 3/8" Thread for Easy Boompole Mounting, 10dB/0dB/+20dB Level Switch, 75Hz Two-step/High-Pass Filter Switch, 40Hz~20,000Hz (selectable HPF@75Hz), 200Ω Output Impedance, Durable Multi-Strand Cable, 1/8" Output Connector, Integrated Foam Windscreen, 1/8" Stereo Mini-jack Output, 9V Battery Powered, Approximate Dimensions 2 1/2" x 4 1/4" x 5", Approximate Weight 4 oz. USA PART NUMBER ELIGIBLE FOR USA MANUFACTURER WARRANTY, NO GRAY MARKET ITEMS, AUTHORIZED DISTRIBUTOR ONLY.

Rode DEADKITTEN, Microphone Cover, Artificial Fur Wind Shield (OR EQUAL):

Furry High-Wind Microphone Cover, Minimizes Wind Noise, Remains Acoustically Transparent, Compatible with Stereo VideoMic/Stereo VideoMic Pro, Approximate Dimensions 3 1/4" x 3 1/8" x 3 1/8", Approximate Weight 1 oz. USA PART NUMBER ELIGIBLE FOR USA MANUFACTURER WARRANTY, NO GRAY MARKET ITEMS, AUTHORIZED DISTRIBUTOR ONLY.

Tascam DR-40, Audio Recorder, Digital, On-Camera DSLR (OR EQUAL):

4-Track, Compact Design, Adjustable Stereo Condenser Mics, Records to SD/SDHC Media, WAV/BWF and MP3 Recording, 12 Ohms Output Impedance, 14 dBV (10 kOhms) Nominal/+2 dBV (10 kOhms) Max. Output Level, XLR and 1/4" Combo Inputs, Phantom Power, USB 2.0 Connector, Integrated Speaker, 3.5mm Headphone/Line Output, 20 mW + 20 mW (32 Ohms) Headphone Output, Battery/100-240VAC/USB Power, 2.5W max. Power Consumption, Black, Includes Mini USB Cable/2GB SD Card/3 x AA Batteries, Approximate Dimensions 3 1/2" x 6" x 1 1/4", Approximate Weight 7 1/2 oz. USA PART NUMBER ELIGIBLE FOR USA MANUFACTURER WARRANTY, NO GRAY MARKET ITEMS, AUTHORIZED DISTRIBUTOR ONLY.

Tascam PS-P520E, AC to USB Power Adapter (OR EQUAL):

External Power Source for Tascam DR-40, 100 - 200 VAC, 50/60 Hz Input Power, 5.0 V, 2 A Output Power, DC to mini-USB Cable. USA PART NUMBER ELIGIBLE FOR USA MANUFACTURER WARRANTY, NO GRAY MARKET ITEMS, AUTHORIZED DISTRIBUTOR ONLY.

Tascam WS-11, Mic Windscreen, Artificial Fur, (OR EQUAL):

Cuts Wind-Noise Pickup by Internal Mics, Works in Both XY and AB Position, Fits TASCAM DR-40 Audio Recorder. USA PART NUMBER ELIGIBLE FOR USA MANUFACTURER WARRANTY, NO GRAY MARKET ITEMS, AUTHORIZED DISTRIBUTOR ONLY.

Polisen HPC-A30, Headphones, Closed-Back Studio Monitor, Studio, Field, Mobile (OR EQUAL):

2" (50mm) Drivers, Closed-Back for Isolation, Pivoting Ear Cups, Collapsible For Easy Storage, Padded Adjustable Headband, Single-Sided 9.8' Cable, Includes 1/4" Adapter, Output Optimized for Mobile

AFRC Combat Camera Senior Leader Kit

Minimum Salient Characteristics

Devices, 32 Ω Impedance, -93 dB \pm 3 dB (@ 1 kHz/mW) Sensitivity, 600 mW Maximum Power, < 5% @ 1 kHz Distortion, 18 Hz to 22 kHz Frequency Response, 9.8' (3 m) Cable, 6.5oz (184g), Black. USA PART NUMBER ELIGIBLE FOR USA MANUFACTURER WARRANTY, NO GRAY MARKET ITEMS, AUTHORIZED DISTRIBUTOR ONLY.

Revo SA-CS-14M, Hot Shoe Adapter, 1/4"-20 Male Post (OR EQUAL):

Attaches to Camera Hot Shoe, Converts Hot Shoe to 1/4"-20 Male Post, Female Hot Shoe and Female 1/4"-20 thread Compatibility, With Locking Disk, Lightweight, Durable Aluminum Material. USA PART NUMBER ELIGIBLE FOR USA MANUFACTURER WARRANTY, NO GRAY MARKET ITEMS, AUTHORIZED DISTRIBUTOR ONLY.

Kopul ACH4-25MON, Line-to-Mic Attenuator Cable (OR EQUAL):

Connects Digital Audio Recorder to DSLR, Attenuates Recorder Output to Mic Level, 1/8" Headphone Tap for Monitoring Signal, 25dB of Attenuation, Premium Shielding to Reduce RF Noise, Straight 1/8" Connectors, 1' Cable Length. USA PART NUMBER ELIGIBLE FOR USA MANUFACTURER WARRANTY, NO GRAY MARKET ITEMS, AUTHORIZED DISTRIBUTOR ONLY.

SanDisk SDSDXP-016G-A46, Memory Card, SDHC, Class 10 (OR EQUAL):

6GB, SanDisk U3, UHS-I/U1/Class 10, 95MB/s Read Speed, 90 MB/s Max Write Speed, 10 MB/s Min Write Speed, Records Full HD Video, Water/Shock/X-Ray Proof, Temperature Proof, Built-In Write-Protect Switch, Downloadable Photo Recovery Software. USA PART NUMBER ELIGIBLE FOR USA MANUFACTURER WARRANTY, NO GRAY MARKET ITEMS, AUTHORIZED DISTRIBUTOR ONLY.

Akitio AK-NEUG-TU3AS-AKTH, Portable Hard Drive, 1 TB, SSD (OR EQUAL):

2.5" SATA Solid State Drive, 520 MB/s Data Transfer Rate, Tethered Thunderbolt Cable (10 Gbps), Micro-USB 3.0 SuperSpeed Port (5 Gbps), Transfer Speeds of up to 10 Gbps, Supports UAS protocol for Increased Performance, Portable and compact design, Bus-powered, High Quality Aluminum for Optimized Heat Dissipation, Approximate Dimensions 5 1/2 " x 3 1/4 " x 3/4 ". USA PART NUMBER ELIGIBLE FOR USA MANUFACTURER WARRANTY, NO GRAY MARKET ITEMS, AUTHORIZED DISTRIBUTOR ONLY.

Case Logic PLS-15, Protective Sleeve, f/u/w15-16" Laptop (OR EQUAL):

Neoprene Exterior and Interior, Suede Lining, Zippered Power Pocket, Dedicated USB Drive Pocket, Black. USA PART NUMBER ELIGIBLE FOR USA MANUFACTURER WARRANTY, NO GRAY MARKET ITEMS, AUTHORIZED DISTRIBUTOR ONLY.

Apple MD862LL/A, 1.6 Ft Thunderbolt Cable, (OR EQUAL):

Two Independent Channels at 10 Gb/s, Total Data Transfer Speed up to 20 Gb/s, Thunderbolt (M) to Thunderbolt (M) Connection, 1.6-Ft. USA PART NUMBER ELIGIBLE FOR USA MANUFACTURER WARRANTY, NO GRAY MARKET ITEMS, AUTHORIZED DISTRIBUTOR ONLY.

Apple MD861LL/A, 6.6 Ft Thunderbolt Cable (OR EQUAL):

Two Independent Channels at 10 Gb/s, Total Data Transfer Speed up to 20 Gb/s, Thunderbolt (M) to Thunderbolt (M) Connection, 6.6-Ft. USA PART NUMBER ELIGIBLE FOR USA MANUFACTURER WARRANTY, NO GRAY MARKET ITEMS, AUTHORIZED DISTRIBUTOR ONLY.

Apple MMEL2AM/A, Thunderbolt 3 to Thunderbolt 2 Adapter (OR EQUAL):

Converts Thunderbolt 3 to Thunderbolt 2, Bi-directional Design, Reversible USB Type-C Connector. USA PART NUMBER ELIGIBLE FOR USA MANUFACTURER WARRANTY, NO GRAY MARKET ITEMS, AUTHORIZED DISTRIBUTOR ONLY.

Apple MJ1K2AM/A, USB-C to Digital AV Multitport Adapter (OR EQUAL):

HDMI, USB Type-C, USB 3.1 Gen 1, For MacBook with a USB Type-C Port. USA PART NUMBER ELIGIBLE FOR USA MANUFACTURER WARRANTY, NO GRAY MARKET ITEMS, AUTHORIZED DISTRIBUTOR ONLY.

AFRC Combat Camera Senior Leader Kit

Minimum Salient Characteristics

Apple MJ1L2AM/A, USB-C to VGA Multitport Adapter (OR EQUAL):

USB Type-C Male Connector, VGA Female Port, USB 3.0 Female Port, USB Type-C Female Port, For MacBook with a USB Type-C Port. USA PART NUMBER ELIGIBLE FOR USA MANUFACTURER WARRANTY, NO GRAY MARKET ITEMS, AUTHORIZED DISTRIBUTOR ONLY.

i5create, JCA141, USB Type-C to 4K DisplayPort Cable, 4 Ft (OR EQUAL):

Aluminum Housing Material, Host Interface USB: Type-C, Male. Video Interface: DisplayPort, Male. Approximate Cable Length 4', Maximum Resolution 3840 x 2160 @ 60 Hz max. Approximate Video Connector Dimensions (W x H x D) 2 x 1 x 1/2". Approximate Weight 1.6 oz. USA PART NUMBER ELIGIBLE FOR USA MANUFACTURER WARRANTY, NO GRAY MARKET ITEMS, AUTHORIZED DISTRIBUTOR ONLY.

Slik 611-352, Mini-Pro V Tripod with 2-Way Pan/Tilt Head (OR EQUAL):

2-way Pan/Tilt Head, Approximate Maximum Height 8 1/2", Approximate Minimum Height 7", Approximate Folded Length 8", Approximate Maximum Load Capacity 3 1/2 lbs., 2 Leg Sections, Locking Ring Leg Lock, Independent Leg Spread, 1 Center Column Section, Sliding Center Column, Approximate Weight 12 1/2 oz., Black. USA PART NUMBER ELIGIBLE FOR USA MANUFACTURER WARRANTY, NO GRAY MARKET ITEMS, AUTHORIZED DISTRIBUTOR ONLY.

Furman SS-6B, Surge Protector, 15-Ft Cord, 6-Outlet, (OR EQUAL):

120V, Heavy-duty Metal Construction, Built-in Circuit Breaker, EMI/RFI Noise Attenuation, Approximate Dimensions 9 1/2" x 3 1/2" x 1 1/2", Approximate Weight 2 3/4 lbs. USA PART NUMBER ELIGIBLE FOR USA MANUFACTURER WARRANTY, NO GRAY MARKET ITEMS, AUTHORIZED DISTRIBUTOR ONLY.

GOAL ZERO Sherpa 100, GZ-42011, Solar Charging Kit (OR EQUAL):

98Wh, 8,800mAh Li-NMC Battery (11V), Charge Small Electronics up to Laptops, Fused to Protect Devices, Nomad 20 Solar Panel, Tri-Fold Design Protects Panels, Weather Resistant, Sherpa 110VAC Inverter, On/Off Switch with LED Power Indicator, Provides One 110VAC Grounded Outlet, USB/12V Power Output, Approximate Weight 2 lbs. USA PART NUMBER ELIGIBLE FOR USA MANUFACTURER WARRANTY, NO GRAY MARKET ITEMS, AUTHORIZED DISTRIBUTOR ONLY.

Lowepr, LP36869, Fastpack BP 250 AW II, Black (OR EQUAL):

Construction Materials-600D nylon, 600D rip-stop, 1680D ballistic base, zipper. Approximate Exterior Dimensions 12 1/4 x 10 1/4 x 19 3/4" Approximate Interior Dimensions 11 1/2 x 6 x 10 3/4". Tripod holder, Waist belt, Shoulder harness, waist belt, top grab handle, trolley handle straps. Approximate Weight: 4 lbs. MANUFACTURER WARRANTY, NO GRAY MARKET ITEMS, AUTHORIZED DISTRIBUTOR ONLY.

Pelican, 015100-0050-110, Carry-On Case with TrekPak Divider System, Black (OR EQUAL):

Exterior Material-High-impact structural copolymer polypropylene resin; Interior-Polyurethane foam, Watertight to 30', O-ring-sealed. Floats in salt water with approximately 64 lb. load. Hinged Closure with double ABS latches And Padlock protectors. Approximate Exterior Dimensions (L x W x D) 22 x 13 3/4 x 9", Approximate Interior Dimensions (L x W x D) 19 3/4 x 11 x 7 1/2", Interior Fitting-1.7 lbs. Polyurethane foam Accommodates Equipment that requires protection from shock and the elements. Front/Side haul handles, Extension handle, Built-in wheels. Approximate Weight 13 1/2 lbs. USA PART NUMBER ELIGIBLE FOR USA MANUFACTURER WARRANTY, NO GRAY MARKET ITEMS, AUTHORIZED DISTRIBUTOR ONLY.